

## ELECTRIC TELESCOPIC BOOM LIFTS

# TB18EJ PLUS (TB590EJ PLUS)/TB20EJ PLUS (TB660EJ PLUS)/TB22EJ PLUS (TB740EJ PLUS)

Compliant with CE/ANSI/CSA/EAC standards

## PRODUCT HIGHLIGHTS

### Green

- Comfortable working environment without noise pollution, meet indoor or emissions-critical site requirements

### Precision Performance

- Three full-scale joysticks for gradual proportional control, Operate with smooth starting and stopping and precision approach to your worksite target
- The Sinoboom IoT system and intelligent 7-inch screen can efficiently control the use and behavior of the equipment

### Economical

- Battery quality assurance, low failure rate and reduced maintenance costs compared with diesel power, which reduces overall operating costs

### Strong Site Passing Performance

- Both the active and inactive states have an oscillating function, allowing work to be performed on inclines and uneven ground



#### Standard Features

Active oscillating function	7-in display screen	4WD x 2WS
Proportional control with 3 joysticks	Automotive-grade sleeves for all pipes	4-wheel brake
Hydraulic platform leveling	160° Platform rotation	Weighing system
Tilt protection system	Max tilt rating to 5°	Emergency stop system
Flashing beacon	Horn & buzzer	Emergency lowering system
Footswitch	2.44m(8') platform	Fault diagnosis system
Foam-filled non-marking tires	Manual storage box	

#### Options & Accessories

AC power to platform	Solid tires	1.45m (4'9") platform
1.83m(6') work platform	2.44m(8') platform with swinging gate	Platform work light
Secondary guarding device	Overhead anti-collision device	Glazier kit(for platform with swinging gate)
Lithium battery	Telematics-ready connector	Half mesh (for platform with swinging gate)

**SINOBOOM™**

**PARTNERS IN ACCESS™**

[SINOBOOM.COM](http://SINOBOOM.COM) | [SALES@SINOBOOM.COM](mailto:SALES@SINOBOOM.COM)

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

**ELECTRIC TELESCOPIC BOOM LIFTS**

**TB18EJ PLUS(TB590EJ PLUS)/TB20EJ PLUS(TB660EJ PLUS)/TB22EJ PLUS(TB740EJ PLUS)**

Compliant with CE/ANSI/CSA/EAC standards

Model	TB18EJ PLUS(TB590EJ PLUS)	TB20EJ PLUS(TB660EJ PLUS)	TB22EJ PLUS(TB740EJ PLUS)
<b>Dimensions</b>			
Max Platform Height	18.4 m (60'4")	20 m (65'7")	22.5 m (73'10")
Max Working Height	20.4 m (66'11")	22 m (72'2")	24.5 m (80'5")
Max Horizontal Reach (Restricted/Unrestricted)	11.7 m/13.2 m(38'5"/43'4")	13.85 m/15.4 m (45'5"/50'6")	12.7m/14.3m (41'8"/46'11")
A Stowed Length	9.67 m (31'8")	9.99 m (32'9")	10.68 m (35'0")
B Stowed Width	2.42 m (7'11")	2.49 m (8'2")	2.49 m(8'2")
C Stowed Height	2.56 m (8'5")	2.79 m (9'2")	2.81m(9'3")
Stowed Length (Transport)	8.71 m (28'7")	8.12 m (26'8")	8.81 m (28'11")
Stowed Width (Transport)	2.42 m (7'11")	2.49 m (8'2")	2.49 m (8' 2")
Stowed Height (Transport)	2.93 m (9'7")	2.77 m(9' 1")	2.93 m (9'7")
D Wheelbase	2.49 m (8'2")	2.49 m(8' 2")	2.49 m (8'2")
Ground Clearance	0.34 m (1'1")	0.39 m(1' 3")	0.39 m (1'3")
Platform Size (L×W×H)	2.44 m×0.91 m×1.1 m(8' × 3' × 3' 7")	2.44 m×0.91 m×1.1 m(8' ×3' ×3' 7 ")	2.44 m×0.91 m×1.1 m (8'×3'×3'7")
<b>Performance</b>			
Max Platform Capacity (Restricted/Unrestricted)	454 kg/300 kg(1,000 lbs/661 lbs)	454 kg/300 kg (1,000 lbs/661 lbs)	454 kg/300 kg (1000 lbs / 661 lbs)
Max Platform Occupants (Restricted/Unrestricted)	3 Persons/2 Persons	3 Persons/2 Persons	3 Persons/2 Persons
Drive Speed (Stowed)	0~4.8 km/h (0~3 mph)	0~4.8 km/h (0~3 mph)	0~4.8 km/h (0~3 mph)
Drive Speed (Raised)	0~1.1 km/h(0~0.68 mph)	0~1.1 km/h(0~0.68 mph)	0~1.1 km/h (0~0.68 mph)
Gradeability	35%	35%	35%
Turntable Rotation	360°/Continuous	360°/Continuous	360°/Continuous
Platform Rotation	160°	160°	160°
Tilt Rating	5°	5°	5°
Turning Radius (Inside/Outside)	2.4 m/4.86 m(7' 10 " /15' 11 " )	2.4 m/5.55 m(7'10"/18' 3")	2.4 m/5.55 m(7'10"/18' 3")
Turntable Tail-Swing	1.15 m(3' 9")	1.45 m (4'9")	1.45 m (4'9")
Max Allowable Side Force	400 N(90 lbf)	400 N (90lbf)	400 N (90 lbf)
Max Allowable Wind Speed	12.5 m/s(28 mph)	12.5 m/s (28mph)	12.5 m/s (28 mph)
Tire Spec/Type	33×12D610 (foam-filled)	355/55D625 (foam-filled)	355/55D625 (foam-filled)
<b>Power</b>			
Drive × Steer	4WDx2WS	4WDx2WS	4WDx2WS
Batteries	48 V, 480 Ah(lead acid battery) 48 V, 500 Ah(lithium battery)	48 V, 480 Ah (lead acid battery) 48 V, 500 Ah (lithium battery)	48 V, 480 Ah (lead acid battery) 48 V, 500 Ah (lithium battery)
Hydraulic Tank Capacity	120 L (26.4 gal(UK)/31.7 gal(US))	180L(39.6 gal (UK)/47.6 gal (US))	180 L (39.6 gal (UK)/47.6 gal (US))
System Voltage	48 VDC	48 VDC	48 VDC
<b>Weight</b>			
Weight	9,600 kg(21,164 lbs)	11,950 kg(26,345 lbs)	12,260 kg(27,029lbs)
Standards Compliance	CE/EAC	CE/ANSI/CSA/EAC	CE/EAC

